












Updated: August 2023

SHINGLES SUPPLY PTY LTD ABN 30 622 446 404  
PO Box 1346 Moss Vale NSW 2575**Tel: 1300 131 881 Int'l: +61 2 9317 3553**  
**Web: shinglessupply.com.au**



Image	Product	Description	Weight	Dimensions	Fixings	Data Sheet	Units	AU\$
<b>Roof Anchors</b>								
	<b>LP06 Corrugator</b>	The Corrugator™ A surface mounted stainless steel roof anchor to suit standard corrugated iron roof sheeting..	165 Grams (without fixings)	295mm x 50mm	1 off M6x50mm Hex Head HG Seal C4 'Roof Zips'; 9 off 15-15x25mm Hex Head HG Seal 'Metal Batten Tek's	<a href="https://www.secureanchor.com.au/roofanchors">https://www.secureanchor.com.au/roofanchors</a>	1	65
	<b>The Corrugator 360</b>	A surface mounted stainless steel roof anchor to suit standard corrugated iron roof sheeting.	235 Grams (without fixings)	175mm x 70mm x 75mm nominal	4 off M6x50mm Hex Head HG Seal C4 'Roof Zips'; 14 off 15-15x25mm Hex Head HG Seal 'Metal Batten Tek's'	<a href="https://www.secureanchor.com.au/roofanchors">https://www.secureanchor.com.au/roofanchors</a>	1	90
	<b>TD06 Trimdek</b>	The TD09 360° fall arrest roof anchor to suit certain roof profiles such as Trimdek®.	310 Grams (without fixings)	120mm x 165mm x 1.2mm nominal foot print	Timber: 8 off M6 x 50mm Hex Head HG Seal C4 'Roof Zips' Sheeting: 8 off 15-15 x 25mm Hex Head HG Seal 'MBTek's' Steel: 8 off M5.5 x 40 Hex Head HG Seal 'Metal Batten Zips'	<a href="https://www.secureanchor.com.au/roofanchors">https://www.secureanchor.com.au/roofanchors</a>	1	90
	<b>SD09 Spandek</b>	A surface mounted stainless steel roof anchor to suit Lysaght Spandek® and Trimdek®.	310 Grams (without fixings)	175mm x 90mm x 1.2mm	16 off 15-15x25mm Hex Head HG Seal 'MBTek's' 6 off 12-24 x 38mm Hex Head	<a href="https://www.secureanchor.com.au/roofanchors">https://www.secureanchor.com.au/roofanchors</a>	1	90
	<b>TV09 Train-Vehicle</b>	A surface mounted stainless steel 'D' ring anchor to suit suitable flat substrates such as train/vehicle roofs and steel columns	350 Grams (without fixings)	60mm x 110mm x 15mm	10 off Stainless Steel 1/4" (6.4mm) Pop Rivets or 10 off M6 15 x 25mm Metal Batten Tek's	<a href="https://www.secureanchor.com.au/roofanchors">https://www.secureanchor.com.au/roofanchors</a>	1	120
	<b>RD08 Flat Pan</b>	A surface mounted stainless steel roof anchor to suit Lysaght Kliplok 700® series trapezoidal ribbed roof sheeting	200 Grams (without fixings)	135mm x 150mm x 165mm	28 off 5-15x25mm Hex Head Metal Batten Tek's	<a href="https://www.secureanchor.com.au/roofanchors">https://www.secureanchor.com.au/roofanchors</a>	1	90
	<b>RD08 Insulated</b>	A surface mounted stainless steel roof anchor to suit insulated sandwich panel roof sheeting.	200 Grams (without fixings)	135mm x 150mm x 165mm	28 off 5-15x25mm Hex Head Metal Batten Tek's	<a href="https://www.secureanchor.com.au/roofanchors">https://www.secureanchor.com.au/roofanchors</a>	1	90
	<b>TA09 Slate &amp; Wood Shingle</b>	A concealed stainless steel 'D' ring anchor for application to the top of a rafter or top chord of a truss	200 Grams (without fixings)	450mm x 50mm	Tile: 6 off M6x50mm Hex Head HG Seal C4 Roof Zips	<a href="https://www.secureanchor.com.au/roofanchors">https://www.secureanchor.com.au/roofanchors</a>	1	70
	<b>TA09-E Extended Tile</b>	A concealed stainless steel 'D' ring anchor for application to the top of a rafter or top chord of a truss	350 Grams (without fixings)	650mm x 50mm	Tile: 6 off M6x50mm Hex Head HG Seal C4 Roof Zips	<a href="https://www.secureanchor.com.au/roofanchors">https://www.secureanchor.com.au/roofanchors</a>	1	115
	<b>RA20 Over Ridge - Shingle</b>	The RA-20 for Asphalt Shingles Only Over Ridge Anchor with a D-ring on both ends	465 Grams (without fixings)	450mm x 65mm	Tile: 6 off M6x50mm Hex Head HG Seal C4 Roof Zips	<a href="https://www.secureanchor.com.au/roofanchors">https://www.secureanchor.com.au/roofanchors</a>	1	110



SHINGLES SUPPLY PTY LTD ABN 30 622 446 404  
PO Box 1346 Moss Vale NSW 2575

**Tel: 1300 131 881 Int'l: +61 2 9317 3553**  
**Web: shinglesupply.com.au**





Image	Product	Description	Weight	Dimensions	Fixings	Data Sheet	Units	AU\$
	<b>RA20-E Over Ridge - All types</b>	Has an attachment point on either side of the ridge. Can be fixed to either onto a minimum 12 mm plywood roof deck or directly to a common rafter	630 Grams (without fixings)	900mm x 65mm x 8mm	6 off Swan Secure Stainless Steel Screws	<a href="https://www.secureanchor.com.au/roofanchors">https://www.secureanchor.com.au/roofanchors</a>	1	120
	<b>CA13 Container</b>	The CA13 fall arrest roof anchor to suit shipping containers.	280 Grams	160mm x 60mm x 60mm nominal	6 off Stainless Steel Ø4" (6.4mm) Pop Rivets (not included) or 6 off M6 15 x 25mm Metal Batten Tekes	<a href="https://www.secureanchor.com.au/roofanchors">https://www.secureanchor.com.au/roofanchors</a>	1	120

### Ladder Brackets

	<b>LP06-LB Corrugator Ladder Bracket</b>	A surface mounted stainless steel bracket to suit Lysaght Custom Orb® corrugated iron roof sheeting	980 Grams	400mm x 470mm x 25mm nominal	2 off M6 x 16mm 304 Stainless steel Hex Head screw 6 off 15-15x25mm Hex Head Metal Batten Tekes	<a href="https://www.secureanchor.com.au/ladderbrackets">https://www.secureanchor.com.au/ladderbrackets</a>	1	165
	<b>TLP22 Tile Ladder Bracket</b>	A surface mounted stainless steel roof support bracket to suit tiled roofs	TBA	Telescopic 550mm to 650mm x 25mm nominal	6 off M6x50mm Hex Head Roof Zips	Tech Sheet Unavailable	1	160
	<b>MP06-LB Multi Profile Ladder Bracket</b>	Flat pan profiles – Trimdek, Kliplok and Longline. Plywood deck for shingle applications	980 Grams	400mm x 470mm x 25mm	3 x 25mm Metal Batten Tekes  For Zink or copper or plywood roofing: Swan Secure screws	<a href="https://www.secureanchor.com.au/ladderbrackets">https://www.secureanchor.com.au/ladderbrackets</a>	1	165
	<b>C20-LB Container Ladder Bracket</b>	A twistlock mounted support bracket to suit shipping containers providing lateral restraint when alighting from the ladder.	850 Grams	500mm x 80mm x 80mm nominal	Twistlock mounted	<a href="https://www.secureanchor.com.au/ladderbrackets">https://www.secureanchor.com.au/ladderbrackets</a>	1	140
	<b>BLB Barge BLBA (Adjustable)</b>	A surface mounted stainless steel roof support bracket to suit right angled metal cappings/fascia	980 Grams	400mm x 270mm x 25mm nominal	12 off 15-15x25mm Hex Head HG Seal Metal Batten Tekes 2 off M6 x 16mm 304 Stainless steel Hex Machine Head Screw	<a href="https://www.secureanchor.com.au/ladderbrackets">https://www.secureanchor.com.au/ladderbrackets</a>	1	165
	<b>SD09-LB Spandek</b>	A surface mounted stainless steel roof support bracket to suit right angled metal cappings/fascia			6 off M6x50mm Hex Head Roof Zips	Tech Sheet Unavailable	1	165

### American Shingles (CertainTeed products)

	<b>Grand Manor</b>	Grand Manor is the top of the line shingle with a multi layered base giving you depth and dimension of aesthetics akin to stone roofing profiles.				<a href="https://www.americanshingles.com.au/files/ugd/1e614b_7434f-04f9eab46b685cd2f220a23bc07.pdf">https://www.americanshingles.com.au/files/ugd/1e614b_7434f-04f9eab46b685cd2f220a23bc07.pdf</a>	m <sup>2</sup>	65
	<b>Belmont</b>	The classic look of slate, masterfully replicated in high performing asphalt shingles.				<a href="https://www.americanshingles.com.au/files/ugd/1e614b_d989a54d8f8f46fe-98346c47497e077b.pdf">https://www.americanshingles.com.au/files/ugd/1e614b_d989a54d8f8f46fe-98346c47497e077b.pdf</a>	m <sup>2</sup>	55



SHINGLES SUPPLY PTY LTD ABN 30 622 446 404  
PO Box 1346 Moss Vale NSW 2575

**Tel: 1300 131 881 Int'l: +61 2 9317 3553**  
**Web: shinglessupply.com.au**



Image	Product	Description	Weight	Dimensions	Fixings	Data Sheet	Units	AU\$
	<b>Highland Slate</b>	Highland Slate's large format four-tab design is expertly engineered to replicate the chiseled form of real quarried slate.				<a href="https://www.americanshingles.com.au/files/ugd/1e614b_e054e-01208064ab698f14d2cc7a10e62.pdf">https://www.americanshingles.com.au/files/ugd/1e614b_e054e-01208064ab698f14d2cc7a10e62.pdf</a>	m <sup>2</sup>	35
	<b>Presidential Shake</b>	The Presidential Series of shingles is created to replicate the look of cedar shakes but with the endurance of asphalt resistance.				<a href="https://www.americanshingles.com.au/files/ugd/1e614b_f64b06f-62c71407fada6c83eb06574c1.pdf">https://www.americanshingles.com.au/files/ugd/1e614b_f64b06f-62c71407fada6c83eb06574c1.pdf</a>	m <sup>2</sup>	50
	<b>Landmark PRO</b>	The Landmark Series of shingles is laminated created to replicate the look of timber shingles with the endurance of asphalt.				<a href="https://www.americanshingles.com.au/files/ugd/1e614b_80d91a27ad2141c-2ba752405920c95cd.pdf">https://www.americanshingles.com.au/files/ugd/1e614b_80d91a27ad2141c-2ba752405920c95cd.pdf</a>	m <sup>2</sup>	35
	<b>XT-25</b>	XT25 shingles are a 'traditional' style shingle with a pattern akin to a brick type pattern.				<a href="https://www.americanshingles.com.au/files/ugd/1e614b_e606bdf-bc7364fb5b8f48a19a74189e8.pdf">https://www.americanshingles.com.au/files/ugd/1e614b_e606bdf-bc7364fb5b8f48a19a74189e8.pdf</a>	m <sup>2</sup>	25
<b>Accessories</b>								
	<b>Solar Support Bracket</b>	SSB works on any part of a plywood deck roof without having to find the structural rafter below.			Can be used on American Shingles Roll-out low slope roofing, Zinc, Copper, Colorbond. Allowed on sandwich refrigeration panels when used as a roof. 6 Swan Secure screws	<a href="https://www.americanshingles.com.au/files/ugd/1e614b_e0a487f765e04d47b54cb8add68b-f92b.pdf">https://www.americanshingles.com.au/files/ugd/1e614b_e0a487f765e04d47b54cb8add68b-f92b.pdf</a>	4	76
	<b>ZILLA Electrical Flashing Assembly</b>	Features a passthrough adapter with 3/4" O.D. NPSM threads and provides a fully flashed, waterproof method of mounting electrical transition components	0.6 kg	14.75" L x 9.75" W x 0.6"H	Hex head, 1/4" x 1-1/2", fits 3/8" socket. Four (4) included.	<a href="https://www.zillarac.com/Portals/0/1 Documents/PDF/Tech/ZillaElectrical_TechSpecs-2016-0826.pdf">https://www.zillarac.com/Portals/0/1 Documents/PDF/Tech/ZillaElectrical_TechSpecs-2016-0826.pdf</a>		75
	<b>ZILLA Double Stud XL Flashing</b>	Attaches to sheathing or structural members for faster, safer and easier installations on composition/asphalt shingle roofs.	1.8 lbs.	15"L x 9-7/8"W x 7/8"H	1/4" x 1-1/2" lags. Eight (8) included.	<a href="https://zillarac.com/Zilla/2014/07/23/Dou-ble-Stud-XL-Flashing-Assembly">https://zillarac.com/Zilla/2014/07/23/Dou-ble-Stud-XL-Flashing-Assembly</a>		
	<b>Winterguard HT Underlay</b>	Winterguard 'Peel & Stick' self adhering, waterproofing underlay (sarking)			Per 18 m <sup>2</sup> Roll	<a href="https://www.americanshingles.com.au/files/ugd/1e614b_3c86530e544008bbddd3d8103032fe.pdf">https://www.americanshingles.com.au/files/ugd/1e614b_3c86530e544008bbddd3d8103032fe.pdf</a>	1	220
	<b>Dimond Deck Underlay</b>	DiamondDeck is a synthetic, scrim-reinforced, water-resistant underlayment that can be used beneath shingle, shake, metal or slate roofing.			Per 75 m <sup>2</sup>	<a href="https://www.americanshingles.com.au/files/ugd/1e614b_e89bc-c5d7ea34b0cb54e2bfa8512b8b8.pdf">https://www.americanshingles.com.au/files/ugd/1e614b_e89bc-c5d7ea34b0cb54e2bfa8512b8b8.pdf</a>	1	300
	<b>Starter Strip</b>	The Starter Strip is the underlying asphalt shingle laid beneath the first course of an American Shingles roof.			Per 34 Lm bundle		1	95

# 4

## PRODUCT LIST



**SHINGLES  
SUPPLY**

SHINGLES SUPPLY PTY LTD ABN 30 622 446 404  
PO Box 1346 Moss Vale NSW 2575

**Tel: 1300 131 881 Int'l: +61 2 9317 3553**  
**Web: shinglessupply.com.au**



Image	Product	Description	Weight	Dimensions	Fixings	Data Sheet	Units	AU\$
	<b>Flintlastic SA Cap</b>	Self-adhered modified bitumen roof system. Flintlastic SA delivers the reliable protection of traditional modified bitumen roofing for a fraction of the labor.			Per 20 m <sup>2</sup> Roll	<a href="https://www.americanshingles.com.au/_files/ugd/1e614b_78192f-3446fa4f51861d04d6be98c57f.pdf">https://www.americanshingles.com.au/_files/ugd/1e614b_78192f-3446fa4f51861d04d6be98c57f.pdf</a>		220
	<b>Flintlastic Ply Base</b>	Flintlastic® SA PlyBase is designed for use as a base ply or inter ply in self-adhering roofing systems.			Per 20 m <sup>2</sup> Roll	<a href="https://www.certainteed.com/resources/RPG_Flintlastic-SA-Ply-Base-TDS.pdf">https://www.certainteed.com/resources/RPG_Flintlastic-SA-Ply-Base-TDS.pdf</a>		180
	<b>Shadow Ridge – Hip &amp; Ridge Caps</b>	Capping shingles provide the ultimate finish to the roof covering all hips, ridges and concealing the ridge vents.			24 x 3 Pice Units (72 shingles) Per Bundle	<a href="https://www.americanshingles.com.au/_files/ugd/1e614b_8ea97af49d79419f8c-83ba6e6d166739.pdf">https://www.americanshingles.com.au/_files/ugd/1e614b_8ea97af49d79419f8c-83ba6e6d166739.pdf</a>	1	95
	<b>High performance Starter</b>	For use with Grand Manor®, Highland Slate® and Belmont® shingles.			Per 34 Lm bundle	<a href="https://www.americanshingles.com.au/_files/ugd/1e614b_7e-969cacfd4c459f97d93a09450ce41a.pdf">https://www.americanshingles.com.au/_files/ugd/1e614b_7e-969cacfd4c459f97d93a09450ce41a.pdf</a>	1	95
	<b>Swift Start</b>	Metric starter shingle is designed specifically for use with Landmark Series shingles.			Per 34 Lm bundle	<a href="https://www.americanshingles.com.au/_files/ugd/1e614b_b061a8c-2d8ea425db2d7a3cc75f2a854.pdf">https://www.americanshingles.com.au/_files/ugd/1e614b_b061a8c-2d8ea425db2d7a3cc75f2a854.pdf</a>	1	95
	<b>9" Filtered Ridge Vent</b>	External wind baffle deflects wind and weather over the vent and creates low pressure above the vent to pull air out of the attic. Class A Fire Rated			EACH	<a href="https://www.americanshingles.com.au/_files/ugd/1e614b_10192f-36c84b4f91b7a62aa0cd9990a9.pdf">https://www.americanshingles.com.au/_files/ugd/1e614b_10192f-36c84b4f91b7a62aa0cd9990a9.pdf</a>	1	14
	<b>12" Filtered Ridge Vent</b>	External wind baffle deflects wind and weather over the vent and creates low pressure above the vent to pull air out of the attic. Class A Fire Rated			EACH	<a href="https://www.americanshingles.com.au/_files/ugd/1e614b_595a-9987f1144711a0a410c842c97d49.pdf">https://www.americanshingles.com.au/_files/ugd/1e614b_595a-9987f1144711a0a410c842c97d49.pdf</a>	1	15
	<b>Rolled ridge vent</b>	External wind baffle deflects wind and weather over the vent and creates low pressure above the vent to pull air out of the attic			Per M <sup>2</sup>	<a href="https://www.americanshingles.com.au/_files/ugd/1e614b_e97c88f52f9b46a68c-5cd934949544f2.pdf">https://www.americanshingles.com.au/_files/ugd/1e614b_e97c88f52f9b46a68c-5cd934949544f2.pdf</a>	1	
	<b>Flashing Drip Edges</b>	The Drip Edges are part of the flashings of the shingle roofing system to prevent the ingress of water and protect the plywood from long term degradation.			3m Length		1	42
	<b>Flashing Barge Strip Edge</b>				3m Length		1	8



# PRODUCT LIST









# SHINGLES SUPPLY

SHINGLES SUPPLY PTY LTD ABN 30 622 446 404  
PO Box 1346 Moss Vale NSW 2575

**Tel: 1300 131 881 Int'l: +61 2 9317 3553**  
**Web: [shinglessupply.com.au](http://shinglessupply.com.au)**



Image	Product	Description	Weight	Dimensions	Fixings	Data Sheet	Units	AU\$
	<b>Flashing SS Step</b>				200mm		1	50
	<b>12mm F 11 Roof Ply Sheeting</b>	(Tongue & Groove) for Roofdeck applications		2400 mm x 1200 mm x 12 mm			1	62
	<b>CRN45A Coil Roofing Nailer</b>	Fastening asphalt and fibreglass shingles	2.6kgs	313mm X 116mm X 271mm	Magazine capacity: 120 nails		1	464
	<b>45mm coil roofing nails</b>	45mm 3.2 gauge Flat Head		Qty: 3600	Wire welded		1	212.5
	<b>45mm coil roofing nails</b>	45mm 3.2 gauge Flat Head		Qty: 7200	Wire welded		1	425
	<b>32mm coil roofing nails</b>	32mm 3.2 gauge Flat Head		Qty: 3600	Wire welded		1	175
	<b>32mm coil roofing nails</b>	32mm 3.2 gauge Flat Head		Qty: 7200	Wire welded		1	350
	<b>25mm coil roofing nails</b>	25mm 3.2 gauge Flat Head		Qty: 3600	Wire welded		1	200
<b>Backpacks</b>								
	<b>27L SafeT Backpack</b>	SafeT-BakPak allows you to carry your equipment safely & securely in four compartments.	1.4kg	Capacity: 27 litres	Hi-vis Yellow	<a href="https://www.secureanchor.com.au/safet-bakpak">https://www.secureanchor.com.au/safet-bakpak</a>	1	95
	<b>20L Safe Cycle backpack</b>	Whether you're on a push bike or a motorcyclist, let others know you're around	500g	Capacity 20 litres	Hi-vis Yellow or Pink	<a href="https://www.secureanchor.com.au/copy-of-safet-bakpak">https://www.secureanchor.com.au/copy-of-safet-bakpak</a>	1	55